



www.secap.com

## Secap® Color Digital Printer

SAY IT WITH COLOR!



Model SL 600

### Setting New Standards in Mailstream Productivity

The Secap® Color Digital Printer is the new cost effective solution for printing on-demand, full color envelopes, cards, and sheets.

- Speeds up to 3,300 full color #10 envelopes per hour, 500,000+ per month
- Print envelopes to 13" x 17" and sheet up to 13" x 22"
- Average consumable cost per full color #10 envelope is only 2¢
- Prints variable data at full speed for optimum productivity
- High capacity sheet feeder holds up to 600 envelopes or 4,000 sheets of 20lb. bond

# Secap® Color Digital Printer

## TECHNICAL SPECIFICATIONS

**Print Method:** Electrophotographic, single pass, digital printer

**Print Speed\*:** From the paper cassette; Color: up to 36 ppm; Monochrome: up to 40 ppm; Envelope Feeder, 60 envelopes

**Warm-up Time:** Up to 85 seconds

**First Page Output Time:** Color: 10.5 seconds from an idle, ready state on plain paper; Monochrome: 9 seconds from an idle, ready state on plain paper

**Resolution:** 600 x 1200 dpi

**Recommended Duty Cycle:** 150,000 prints per month maximum (industry standard letter/A4 at 5%)

### HARDWARE AND SOFTWARE CAPABILITIES

**Processor Type:** PowerPC 750FX, 800 MHz

**Memory:** 1 GB standard

**Operating System Compatibility:** Windows: Windows® XP Professional, XP Home, 2003 Server; Windows 98, 98 SE, ME, NT® 4.0 Workstation, NT 4.0 Server (SP6 or later), 2000 Workstation (SP3 or later), 2000 Professional (SP3 or later), 2000 Server (SP3 or later), 2000 Advanced Server (SP3 or later); Citrix® MetaFrame® – Windows 2000 Server (ServicePack4) with Citrix MetaFrame XP® Presentation Server Feature Release 3, Windows Server 2003 Standard Edition with Citrix MetaFrame XP Presentation Server Feature Release 3; Macintosh: Mac® OS 9.x, Mac OS 10.2.4 – 10.4.2; Unix/Linux

**Printer Languages:** Adobe PostScript 3, PDF v.1.4 Emulations: PCL®5c, PCL 6, IBM PPR, EPSON FXDirect PDF Printing (Windows only) Printer Management: Printer Drivers, Color Correct Utility, Color Swatch Utility, PDF Direct Print, Profile Assistant, PS Gamma Adjuster, Storage Device Manager, Admin Manager/Quick Setup, LPR Utility, Network Printer Status

### INTERFACE SUPPORT

**Standard:** 10/100-TX Ethernet, High-speed USB v2.0, Parallel

**Ethernet Protocols:** TCP/IP, Netware and Ethertalk. TCP/IP includes ARP, IP, ICMP, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMP, DNS, SSL/ TLS, JetDirect protocols; Netware includes 3.x, 4.x, 5.x, and 6.x with full NDS and NDPS support – PServer, RPrinter, NDPS supported via dedicated NDPS Gateway. EtherTalk: ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP.

\*Print Speed varies depending on system configuration, software application, driver, thickness of stock and document complexity. Specifications subject to change without notice.

### PAPER HANDLING

**Standard Paper Input:** 530 sheets + universal tray

**Envelope Input Feeder:** 600 Com #10 envelopes; 4,000 sheets (20lb bond)

**Delivery Stacker:** Variable speed conveyer belt

Paper Size Supported: Universal Tray: Tabloid extra (12" x 18"), tabloid, legal, letter, executive, index cards, A3, A3 wide (12.6" x 17.7"), A3 outsize (12.9" x 17.8"), A4, A5, A6, B4, B5, C5, DL; Feeder: Sheets and Envelopes (min: 5.125" x 4.125" or 130.2mm, max: 13" x 22" or 330.2mm x 558.8mm) Paper Weights: Universal Tray supports 75-216 gsm, up to 50 lb. text and 80 lb. cover; Feeder supports 75-308 gsm, up to 14 point cover

**Print Media:** Plain paper, letterhead, coated, uncoated, linen, specialty stocks

**Window Envelopes:** Glassine, Earth First PLA, Digi-Clear™, open window (Poly Window Envelopes are NOT supported)

### PHYSICAL

**Type:** Digital envelope press with internal Adobe PostScript controller

**Dimensions (WxDxH):** including delivery conveyer; 92" x 24.4" x 18.2" (233 cm x 62.0 cm x 46.2 cm)

**Weight:** 152 lb. (69.0 kg) without options

### ELECTRICAL

**Power Requirements:** 120 (110 – 127) VAC; 60 Hz ± 2 Hz; 230 (220 – 240) VAC; 50 Hz, ±2 Hz

**Power Consumption:** Operating: 750W; Standby: 200W; Power Save Mode: 55W

### ENVIRONMENTAL

**Temperature Requirements:** Operating: 50-90° F (10-32° C); Non-operating: 32-110° F (0-43° C); Best Print Quality: 63-80° F (17-26° C)

**Humidity:** Operating: 20-80% RH; Non-operating: 10-90% RH; Best Print Quality: 50-70% RH

**Noise Levels:** Operating: 53 dB; Standby: 40 dB; Power Save Mode: 40 dB

### CONSUMABLES

**In-Box Cartridges:** Printer ships with one each cyan, magenta, yellow and black toner cartridge; cyan, magenta, yellow and black image drum; waste toner box, fuser unit, and transfer belt


### TYPEFACES

136 Adobe PostScript Type 1 typefaces, 86 scalable PCL fonts, 1 bitmap font, 10 TrueType® fonts, OCR A/B, USPS Barcode



10 Clipper Road  
West Conshohocken, PA 19428-2721  
800.523.0320  
610.825.6205  
610.825.1397 (fax)  
www.secap.com

Available from your authorized and certified Secap dealer.



Contact the dealer above or call 800.523.0320 for a Secap dealer near you.

© Xante, Symphony Workow, SpeedSetter, KoolKolor, KoolToning, StripRITE, PerfectBLEND, AdvancedScan, RasterView, TrapZone, ImagerQ Concerto, VM, Harmony Violet Metal Plates, Harmony Violet CTP Developer, Harmony Violet CTP Replenisher, Harmony Litho Processor Cleaner, and Harmony Litho CTP Gum are trademarks or registered trademarks of Xanté Corporation. Adobe, PostScript 3, APPE and Accurate Screens are registered trademarks of Adobe Systems, Incorporated, which may be registered in certain jurisdictions. Fiery is a registered trademark of EFI. All other trademarks or registered trademarks are the property of their respective owners. Prices and equipment specifications subject to change without notice